



30

HUDSON STREET
JERSEY CITY

SPECIFICATIONS

ARCHITECT:

Cesar Pelli & Associates

YEAR BUILT:

2004

CERTIFICATIONS:

LEED and ENERGY STAR certified

NUMBER OF STORIES:

40 stories

SPACE AVAILABLE TO LEASE:

Floors 9 & 10; 36 - 40
Currently fully furnished

TYPICAL FLOOR RENTABLE AREA:

Tower floors: +/-33,500 RSF to +/- 36,500 RSF
Low-rise floors: +/- 36,500 RSF

TYPICAL CEILING HEIGHT:

Slab-to-slab height of 14'6"
Floor to finished ceiling height 9' 6"

RAISED FLOOR:

8"

WINDOW MULLION:

5' on center except corners where spacing varies

LIVE FLOOR LOAD:

50 pounds per square foot

INTERIOR COLUMN SPACING:

No interior columns

CORE TO EXTERIOR WALLS:

Minimum of 50 feet

ON-SITE AMENITIES:

Full service cafeteria with 440 seats
Fitness center with locker rooms
Parking garage below grade
Lobby coffee bar
Public plaza with outdoor seating area
Free ATM onsite
Ground floor retail
Access to Pier and PATH

BUILDING INFRASTRUCTURE:

The building was designed to limit the possibility of business interruption by providing a high level of redundancy for all critical systems. Emergency power systems, fuel oil and water reservoirs as well as multiple locationally diverse utility and telecom feeds achieve reliable and resilient operation capabilities. A robust rapid deployment flood mitigation system is located on-site and can be fully deployed in less than 3 hours.

HEATING VENTILATION AND AIR CONDITIONING (HVAC):

Central water cooled chiller plant provides heat rejection for building Air Handling Units (AHUs) feeding tenant floors via common supply and return air duct risers. HVAC system is capable of both air-side and water-side economizer (free cooling) operation. All air handling units are equipped with MERV-14 filters and ventilation rates exceed both the USGBC LEED Enhanced Indoor Air Quality (IAQ) and the WELL Building Ventilation Standards. HVAC systems are monitored at central BMS which is manned 24/7/365.

HOURS OF HVAC OPERATION:

Base building HVAC provided from 8am to 6pm Monday through Friday. Overtime HVAC is available and is charged at prevailing market rates.

POWER:

30 Hudson is fed from three (3) distinct 26kv feeders provided by the local utility (PSE&G). The three (3) feeders serve the building's interior spot networks on the 14th Floor of the building (alleviating any flooding concerns of building electrical systems.) Only two (2) of the three (3) feeders are required to serve the building at full load. Standard floor power consists of 4.5 watts (3 watts power and 1.5 watts lighting) per usable square foot for utility and lighting (excluding HVAC).

EMERGENCY GENERATOR/BACK UP POWER:

Eight (8) 2000 kW generators, supported by four (4) 22,500 fuel storage tanks, provide full load support for the entire building's electrical load for up to five days. Emergency power distribution includes 48 closed-transition automatic transfer switches.

TELECOMMUNICATIONS:

The telecommunications infrastructure is robust and allows for significant redundancy and flexibility. Principal features include: 2 diverse points of entry to the building for tenants, 2 diverse vertical risers for carriers, 2 diverse vertical risers for internal floor to floor cabling, roof access – pathway to roof available through riser.

Hope G. Brodsky
hbrodsky@ngkf.com
201.460.5110

Harrison Russell
hrussell@ngkf.com
201.504.5171

Hal Stein
hstein@ngkf.com
212.233.8185

Neil J. Goldmacher
ngoldmacher@ngkf.com
212.372.2153

NEWMARK

No warranty or representation, express or implied, is made as to the accuracy of the information contained herein, and same is submitted subject to errors omissions, change of price, rental or other conditions, withdrawal without notice, and to any specific listing conditions, imposed by our principals.